



Superior Solutions

PROD. #1301
408

PRODUCT SPECIFICATION REPORT

ZEP C-SOLV™ Non-emulsifying Cleaner and Degreaser

DESCRIPTION

A non-emulsifying, non-chlorinated, solvent degreaser that is a blend of natural, citrus solvents, grease-dispersing agents, and high-flash solvents.

FEATURES

- Formulated with natural citrus solvent
- Powerful solvent action
- Versatile use
- Non-emulsifying

BENEFITS

- Environmentally desirable and pleasant to use, no overwhelming solvent odor.
- Strong solvents quickly dissolve grease and oil from concrete, metal and other hard surfaces.
- May be used for general degreasing, tank cleaning and electric motors.
- Able to be used as a floating degreaser

APPLICATIONS

Use as a degreaser for windings, breakers, bushings, bearings, electric motors, industrial equipment on concrete, metal and other hard surfaces.

COMPANION PRODUCTS

Zep 70, Zep Soy Foam, Zep Fast Gasket Makers, Zep Threadlockers, Zep Formula 166, Zep Restore, Zep Soy Punch, Zep Shell Shock

SPECIFICATIONS

Physical Form	liquid	Flash point (TCC)	144° F (62.20C)
Odor	citrus	pH	N/A
Color	colorless to light yellow	Shelf Life.....	1 year minimum
Specific Gravity0.82	D.O.T. Shipping Label.....	None

PACKAGING

- 1 gallon
- 4 gallon case
- 5 gallon pail
- 20 gallon container
- 55 gallon container

Zep Sales & Service, a unit of Zep Inc.

1-877-I BUY ZEP
(1-877-428-9937)



Superior Solutions

PRODUCT LABEL

PROD. #1301
408

ZEP C-SOLV™ Non-emulsifying Cleaner and Degreaser

BEFORE USING THIS PRODUCT, PLEASE READ THIS ENTIRE LABEL

PROD. #1301 607G



C-SOLV™

NON-EMULSIFYING INDUSTRIAL DEGREASER

Zep C-Solv is a non-emulsifying blend of natural citrus and aliphatic solvents. Excellent for many cleaning and degreasing applications, including electric motors, windings, breakers, bushings and bearings. It is especially useful for degreasing applications where the oil/water is to be reprepared for disposal. The dielectric strength of Zep C-Solv is 46,000 volts as determined by ASTM D877-84a.

DIRECTIONS:
General Degreasing: Apply Zep C-Solv undiluted to surface to be cleaned. Allow to soak until grease and oil are loosened, rinse with pressure washer or strong stream of water. If runoff is contained and allowed to stand, the oil and water will reseparate into two layers which will facilitate disposal.
Tank Cleaning: Apply undiluted to inside of tank with a brush or low pressure spray. Let soak to loosen greas. Rinse with high pressure or a strong stream of water.
Electric Motors: Use undiluted. Spray or wipe onto surface to be cleaned. After cleaning and before restarting, force out remaining solvent with compressed air.

NOTE: Product is combustible, having a flash point of 34.40° F. When using Zep C-Solv, avoid possible sources of ignition, or before restarting electric motors, solvent must be completely evaporated.
As a floating degreaser: Pour enough Zep C-Solv on top of effluent to create a 1/2 inch to one-inch thick layer of product (usually between 1/4 to 1/2 gallon of product per square foot).

NOTE to customers in California, Lake Michigan Air Directors Consortium (LADCO) states, and Ozone Transport Commission (OTC) states: This product is sold to and is to be used exclusively by establishments which manufacture or construct goods or commodities.

DANGER!
COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED

**KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY**


See Back Panel For Additional Precautionary Statements.

140067 234433
NET CONTENTS: 1 U.S. GALLON (3.78 L) S608

Proudly American Made
ZEP MANUFACTURING COMPANY
 A division of Acuity Specialty Products Group, Inc.
 ATLANTA, GA 30301
 CLEAN ACROSS AMERICA AND THROUGHOUT THE WORLD™
 AcuityBrands

BEFORE USING THIS PRODUCT, PLEASE READ THIS ENTIRE LABEL

PROD. #1301 607G



C-SOLV™

NON-EMULSIFYING INDUSTRIAL DEGREASER

DANGER!

COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED

Can cause eye irritation. Prolonged or repeated contact may cause skin irritation. Potential skin sensitizer. Inhalation of vapors may cause respiratory tract irritation and/or central nervous system depression characterized by headache, dizziness, nausea or stupor. DO NOT swallow this product. Avoid breathing vapors. Exposure may aggravate existing skin or respiratory disorders. Further information on the effects of overexposure is included on the Material Safety Data Sheet, which is available upon request.

Zep advocates limiting exposure to all chemical products. DO NOT swallow this product. Zep recommends wearing safety glasses during product use and handling. The use of rubber, nitrile, neoprene, or other resistant gloves is strongly recommended for prolonged use.

Remove contaminated clothing promptly and DO NOT rewear until thoroughly cleaned. After handling, wash hands thoroughly with soap and water.

FIRST AID:
EYES: immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
SKIN: Wash affected area immediately and thoroughly with soap or mild detergent. Consult a physician if irritation develops.
INHALATION: Move exposed person to fresh air. If irritation persists, get medical attention immediately.
INGESTION: If this product is swallowed, DO NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration (breathing) of liquid into the lungs. Get emergency medical attention immediately.

DISPOSAL AND/OR SPILL INFORMATION: As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted to a collection vessel, or where permitted, to a sanitary sewer (consult local and state regulations) and not allowed to soak into the ground or to enter a storm sewer. If this product is spilled or contained and cannot be used, creating the need for disposal, absorb product on an inert absorbent material, such as Zep-Q-Zorb or Zep Super Sorbent, and deposit in a clean, sealable container for disposal. Thoroughly clean area with a detergent solution and rinse area well with water.

COMBUSTIBLE: Keep away from heat, spark, open flame or any source of ignition. Store in a cool area away from direct sunlight. Keep container tightly closed at all times when not in use to decrease evaporation of volatile solvents. Keep this product away from food and food products. Store tightly closed container in dry area at temperatures between 40°F (4°C) and 120° F (29°C).

PRECAUCIÓN
AL USUARIO: Si usted no lee Inglés, no use este producto hasta que la etiqueta le haya sido explicada ampliamente. **(TO THE USER:** If you cannot read English, do not use this product until the label has been fully explained to you.)

HMIS RATINGS		
HEALTH	2	4 EXTREME
FLAMMABILITY	2	3 SERIOUS
REACTIVITY	0	2 SLIGHT
PERSONAL PROTECTION EQUIPMENT	B	0 MINIMAL
		Glasses, Gloves

W608

This product is designed exclusively for industrial and institutional use by trained, professional maintenance personnel. Label directions and precautions must be followed exactly. Zep Manufacturing Company will not be responsible for any injury, loss, or damage, if product is used in any manner not in compliance with label directions, or if precautions are not observed.

1-877-1 BUY ZEP (1-877-428-9937)