



Armor All® Professional  
 A unit of Zep Inc.  
 P.O. Box 2015  
 Atlanta, GA 30301  
 1-866-ARMORALL (276-6725)  
 www.armorallpro.com

# Material Safety Data Sheet

## Section 1. Chemical Product and Company Identification

**Product name** AAP SUPER CONC WHEEL & TIRE CLNR  
**Product use** Automotive Wheel Cleaner  
**Product code** H401  
**Date of issue** 09/30/08 **Supersedes** 01/27/03

### Emergency Telephone Numbers

**For MSDS Information:**

Armor All Customer Service 1-866-276-6725

**For Medical Emergency**

INFOTRAC: (877) 541-2016 Toll Free - All Calls Recorded

**For Transportation Emergency**

CHEMTREC: (800) 424-9300 - All Calls Recorded  
 In the District of Columbia (202) 483-7616

Printing date: 10/02/08

### Prepared By

Compliance Services  
 1420 Seaboard Industrial Blvd.  
 Atlanta, GA 30318

## Section 2. Hazards Identification

### Emergency overview

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

**DANGER !**



CAUSES EYE AND SKIN BURNS. HARMFUL IF SWALLOWED.  
 HARMFUL IF ABSORBED THROUGH SKIN.

**NOTE:** MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

### Acute Effects

### Routes of Entry

Dermal contact. Eye contact. Inhalation.

**Eyes**

Causes eye burns. Eye exposure may cause severe and permanent eye injury (blindness).

**Skin**

Causes skin burns. The amount of tissue damage depends on length of contact. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

**Inhalation**

Avoid breathing vapors, spray or mists. Over-exposure by inhalation may cause respiratory irritation.

**Ingestion**

Harmful if swallowed. May cause burns to mouth, throat and stomach.

Contains material which may cause damage to the following organs: kidneys, lungs, liver, blood. Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness.

**Carcinogenicity** Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

**Additional Information:** See Toxicological Information (Section 11)

## Section 3. Composition/Information on Ingredients


<u>Name of Hazardous Ingredients</u>	<u>CAS number</u>	<u>% by Weight</u>
TETRASODIUM ETHYLENEDIAMINE TETRAACETATE; ethylenediamine tetraacetic acid; tetrasodium salt	64-02-8	10 - 20
MONOETHANOLAMINE; 2-aminoethanol; MEA	141-43-5	5 - 15
ALCOHOLS, C9-11, ETHOXYLATED; linear primary alcohol ethoxylate	68439-46-3	1 - 10
ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve	111-76-2	1 - 10
SODIUM METASILICATE; silicic acid (H2-Si-O3) disodium salt; water glass	6834-92-0	<5
SODIUM XYLENE SULFONATE	1300-72-7	1-10

**Section 4. First Aid Measures**

<b>Eye Contact</b>	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
<b>Skin Contact</b>	Flush affected area immediately with large amounts of water for at least 15 minutes. Get medical attention immediately.
<b>Inhalation</b>	Move exposed person to fresh air. If irritation persists, get medical attention.
<b>Ingestion</b>	Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If affected person is conscious, give plenty of water to drink. Get medical attention immediately.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)



<b>Flash Point</b>	Closed cup: >93.33°C (>200°F)
<b>Flammable Limits</b>	Not available.
<b>Flammability</b>	Non-combustible.
<b>Fire hazard</b>	In a fire or if heated, a pressure increase will occur and the container may burst.
<b>Fire-Fighting Procedures</b>	Use an extinguishing agent suitable for the surrounding fire.

**Section 6. Accidental Release Measures**

<b>Spill Clean up</b>	Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
-----------------------	---

**Section 7. Handling and Storage**

<b>Handling</b>	Put on appropriate personal protective equipment (see section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Use with adequate ventilation. Do not ingest. Wash thoroughly after handling. Do not reuse container.
<b>Storage</b>	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

MONOETHANOLAMINE; 2-aminoethanol; MEA

ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve

SODIUM METASILICATE; silicic acid (H2-Si-O3) disodium salt; water glass

**Exposure limits****OSHA PEL / ACGIH TLV (United States).**

TWA: 3 ppm 8 hour(s).

**OSHA /ACGIH (United States).**

STEL: 6 ppm 15 minute(s).

**ACGIH TLV (United States).**

TWA: 20 ppm 8 hour(s). Form:

**OSHA PEL (United States). Skin**

TWA: 50 ppm 8 hour(s). Form:

**Supplier Suggested (United States).**CEIL: 2 mg/m<sup>3</sup> Form:**Personal Protective Equipment (PPE)**

<b>Eyes</b>	Splash goggles. Face shield.
<b>Body</b>	Wear appropriate protective clothing to prevent skin contact. Recommended: Neoprene gloves. Rubber gloves. Nitrile gloves. Synthetic apron. Chemical resistant boots.
<b>Respiratory</b>	Avoid breathing vapors, spray or mists. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of below established levels. Wear appropriate respirator when ventilation is inadequate.

**Section 9. Physical and Chemical Properties**

<b>Physical State</b>	Liquid.	<b>Color</b>	Clear. Light. Amber.
<b>pH</b>	12.5 - 13.0	<b>Odor</b>	Slight Butyl
<b>Boiling Point</b>	100°C (212°F)	<b>Vapor Pressure</b>	Not determined.
<b>Specific Gravity</b>	1.09	<b>Vapor Density</b>	Not determined.
<b>Solubility</b>	Easily soluble in the following materials: cold water and hot water.	<b>Evaporation Rate</b>	1 (Water = 1)
		<b>VOC (Consumer)</b>	241.35 (g/l). 2.01 lbs/gal 22.18%

**Section 10. Stability and Reactivity**

<b>Stability and Reactivity</b>	The product is stable.
<b>Incompatibility</b>	Slightly reactive or incompatible with the following materials: oxidizing materials and acids.
<b>Hazardous Polymerization</b>	Will not occur.
<b>Hazardous Decomposition Products</b>	carbon oxides (CO, CO <sub>2</sub> ) and oxides of nitrogen

**Section 11. Toxicological Information****Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Tetrasodium Ethylenediamine Tetraacetate	LD50 Oral	Rat	4100 mg/kg	-
Monoethanolamine	LD50 Dermal	Rabbit	>1000 mg/kg	-
	LD50 Oral	Rat	1720 mg/kg	-
Ethoxylated Alcohols	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1400 mg/kg	-
Ethylene Glycol Monobutyl Ether	LD50 Dermal	Guinea pig	>2000 mg/kg	-
	LD50 Oral	Guinea pig	1200 mg/kg	-
	LC50 Inhalation Vapor	Guinea pig	>633 ppm	1 hours
Sodium Metasilicate	LD50 Oral	Rat	1153 mg/kg	-
	LD50 Oral	Mouse	770 mg/kg	-

**Section 12. Ecological Information**

**Environmental Effects** No known significant effects or critical hazards.

**Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Code: D002  
Classification: - [Hazardous waste]  
Origin: - [RCRA waste.]

**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
<b>DOT Classification</b>	Not regulated.	Not a DOT controlled material (United States).			
<b>IMDG Class</b>	Not determined.				

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

**Product name**

Ethylene Glycol Monobutyl Ether

**Clean Water Act (CWA) 307:** No products were found.

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations**

**California Prop 65** No products were found.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.